

EX SERIES ATTACHMENT EX57



CONTACT US 336-584-6700 | WORDROCKDRILLS.COM

DETAILS

- Boom or Stick Mounting Capabilities
- Supplied with Hydraulic Quick Couplers for Easy Installation
- 360 Mast Movement
- Dual Axis Movement Option
- Interchangeable Drifters
- Variety of Feed Lengths Available
- Radio Remote Control with Autodrill Feature
- Utilizes Hydraulic Auxiliary of Excavator



TECHNICAL SPECIFICATIONS

Operating Requirements	≥ 30 gpm at 2,800 psi
Flushing Medium	Air, Water, Grout
Push/Pullback	7,000lbs (14,000kbs w/ Dual Feed System)
Air Flushing Volume	375cfm
Air Flushing Pressure	150psi
Thread Type	2-3/8" IFP -> 2-3/8" API Reg Box
Max Hole Size	10"
Rotary RPM	60 - 80rpm @17gpm
Electrical Requirements	24v/12v
Stroke Length	12 - 21 ft (Custom Options Available)
Width, Height	70", 70"
Rotation Torque	1750 ft/lb @ 2800psi
Weight	5,000lbs
Air Valve Pressure Rating	150 psi
Carrier Size	8 Ton Excavator Minimum Recommended