

# RTG RG 21T



## OVERVIEW

Used RTG RG 21T Serial Number 376. This leader and pile driving rig is pre-equipped for driving piles and sheets with a MR 150 AVM variable moment vibratory hammer (MR 150 AVM hammer included). It is also pre-equipped for drilling for use with an MB 50 to MB 155 rotary (rotary **not** included). It is also pre-equipped for impact hammer (Fambo HR5000 included). The rig is built on a BS 65 RS Base Carrier with a 755 hp (563 kW) CAT C 18 Tier 4f engine. Special feature is the silent vibro technology.

## SPECIFICATIONS

<b>Serial Number</b>	376
<b>Year of Manufacture</b>	2020
<b>Rig Hours</b>	1935 hours (as of 8/27/2024)
<b>Transport Weight</b>	136,000 lbs + 1 fall off load
<b>Vibratory Hammer</b>	<ul style="list-style-type: none"> <li>- MR 150 AVM</li> <li>- Silent Vibro</li> <li>- Variable Moment</li> </ul>
<b>Pile Driving Capabilities</b>	- Max Length of Pile = 70 ft (21.4m)
<b>Stone Column Capabilities</b>	- VIPAC up to 50 ft (15.2m)
<b>Rotary Drilling Heads</b>	<ul style="list-style-type: none"> <li>- Up to MB 155</li> <li>- High Speed Rotary Heads</li> <li>- Max Torque = 111,000 ft-lb (150 kNm)</li> </ul>
<b>CFA/Pre-drilling Capabilities</b>	<ul style="list-style-type: none"> <li>- Max Drill Depth = 67 ft (20.4m)</li> <li>- Max Auger Diameter = 30 in (750mm)</li> </ul>
<b>FDP Drilling Capabilities</b>	<ul style="list-style-type: none"> <li>- Max Drill Depth = 67 ft (20.4m)</li> <li>- Max Diameter FDP = 18 in (450mm)</li> </ul>
<b>SCM Drilling Capabilities</b>	<ul style="list-style-type: none"> <li>- Max Drill Depth = 66 ft (20.2m)</li> <li>- Max Diameter SCM = 7 ft (2100mm)</li> </ul>

## AVAILABLE FOR SALE

Sale price is \$ 1,750,000 USD plus tax and freight from NYC area.

**\*\* Includes rig, MR150AVM silent vibro & Fambo HR5000 impact hammer**

