

# SS SERIES ATTACHMENT

## SS57



**CONTACT US** 336-584-6700 | [WORDROCKDRILLS.COM](http://WORDROCKDRILLS.COM)

### DETAILS

- 2 Side Drilling Accessibility
- 110 Degrees of Movement from Horizontal to Vertical
- Variety of Feed Lengths Available
- Interchangeable Drill Head Options
- Utilizes Hydraulic Auxiliary of Skid Steer
- Manual Hydraulic Proportional Controls
- Optional Radio Remote Control Available



### TECHNICAL SPECIFICATIONS

Operating Requirements	>= 30gpm at 2,800 psi
Flushing Medium	Air, Water, Grout
Push/Pullback	7,000lbs (14,000kbs w/ Dual Feed System)
Air Flushing Volume	>= 375cfm
Air Flushing Pressure	150psi
Thread Type	2-3/8" IFP -> 2-3/8" API Reg Box
Max Hole Size	10"
Rotary RPM	60 - 80rpm @17gpm
Maximum Drill Depth	100 ft
Length	12 - 15 ft (Custom Option Available)
Width, Height	70", 70"
Rotation Torque	1750 ft/lb @ 2800psi
Weight	3,000lbs
Feed/Rotation Flow Relief Valve w/ Quick Connect Pressure Unload Valve	
Hydraulic Quick Connects Required: Supply, Return, Case Drain	